



## Gasoline Tuning Chart Sunoco to Rockett™ Brand

<u>Sunoco Product / S. G.</u>	<u>Rockett™ Brand / S. G.</u>	<u>Tuning Suggestions</u>
Sunoco Standard / 0.728	Rockett 112 / 0.721	Richen Mixture by 1 Jet Size
Sunoco Supreme / 0.713	Rockett 114 / 0.727	Lean Mixture by 1 Jet Size
Sunoco HCR Plus / 0.738	Rockett 114 / 0.727	Richen Mixture by 1 Jet Size
Sunoco Maximal / 0.706	Rockett 118 / 0.700	No Change
Sunoco Max N.O.S. / 0.730	Rockett 118 / 0.700	Richen Mixture by 3 Jet Sizes
Sunoco GT 100 Unleaded / 0.768	Rockett 100 Unleaded / 0.719	Richen Mixture by 4 Jet Sizes
Sunoco GT Plus Unleaded / 0.757	Rockett 100 Unleaded / 0.719	Richen Mixture by 3 Jet Sizes

Note: A change in a Holley jet size by 0.001 inches results in a fuel flow change of 2.4%

**WHEN IN DOUBT, GO RICHER**

**For more information or your nearest Rockett™ Brand Distributor, call or click:**  
**1-800-345-0076 / [www.rockettbrand.com](http://www.rockettbrand.com)**